

## TECHNICAL DATA SHEET COMBIFIX<sup>®</sup>-XL

### PRODUCT LINE

**10 V 8054 FOR WATER WITH A BICARBONATE CONTENT ABOVE  
400 PPM**

### APPLICATION

COMBIFIX<sup>®</sup>-XL is intended for use in alcohol dampening systems in sheet-fed offset. If 4% of COMBIFIX<sup>®</sup>-XL is added in alcohol dampening systems, no more than 8 – 10% isopropanol is required.

### SPECIAL CHARACTERISTICS

- Formation of a stable film of dampening solution.
- Specific adjustment of surface tension.
- Very good protection of printing plates.
- Corrosion-certified according to the latest standard. FOGRA approved.

### PROPERTIES

| Product Line | Dosage                | pH        | Conductivity                                 |
|--------------|-----------------------|-----------|--|
| 10 V 8054    | 4% (4-5 oz/US gallon) | 5.0 – 5.3 | 800 – 1000<br>above water,<br>before alcohol |

### PACKAGING

|              |                |         |
|--------------|----------------|---------|
| Plastic Jug  | 2.5 US gallon  | 9.46 L  |
| Plastic Jug  | 5.0 US gallon  | 18.9 L  |
| Plastic Drum | 55.0 US gallon | 208.1 L |