

## TECHNICAL DATA SHEET HYDROFILM W/B FLEXO

### APPLICATION

Premium ink system, specially formulated for running on Film substrates.

### SPECIAL CHARACTERISTICS

- Fast drying on press to allow for higher press speeds
- Low odour
- Low viscosity allowing for excellent on press stability
- Good dry rub resistance to avoid smearing and print set-off
- Additives available as required, to customize to specific press conditions
- Good adhesion to film substrates, suitable for coating and lamination

### PROPERTIES

<b>HEAT RESISTANCE</b>	:	160 – 220 DEGREES C
<b>LIGHTFAST RATING</b>	:	MINIMUM BLUE WOOL SCALE – 3
<b>SHIPPING VISCOSITY</b>	:	26 – 34 SECONDS #2 ZAHN CUP AT 20C
<b>PH RANGE</b>	:	8.6 – 9.4
<b>VISCOSITY ADJUSTER</b>	:	FAST – WATER/ ISOPROPANOL MIX
	:	SLOW – WATER/ PROPYLENE GLYCOL MIX
	:	REGULAR – WATER

\*\*\*Pre-testing with specific substrate is strongly recommended to ensure proper ink performance

### PACKAGING

Plastic Jugs	4kg	8.8 lb
Plastic Kits	18 kg	39.6 lb
Drums	200 kg	440 lb