

## TECHNICAL DATA SHEET HYDROTOP W/B FLEXO

### APPLICATION

An ink system for high quality printing in a wide variety of applications including Folding Carton, Tag and Label, and Consumables Packaging, amongst others. Recommended strongly for paper and board substrates.

### SPECIAL CHARACTERISTICS

- Modular system based upon colour concentrates with mixing varnish tailored for process printing and line work
- Designed to impart maximum gloss and colour strength for fine line anilox printing, while offering enhanced resistance properties and low odour
- Formulated to run with increased press speeds and for general ease of use on press
- Compatible with both rubber and photopolymer type plates
- Lightfast (LF) Series available for both Process and Blend Bases

### PROPERTIES

<b>HEAT RESISTANCE</b>	:	160-220 DEGREES C
<b>LIGHTFASTNESS</b>	:	GENERAL - MINIMUM BLUE WOOL SCALE - 3 LF SERIES – MINIMUM BLUE WOOL SCALE - 5 TO 6
<b>SHIPPING VISCOSITY</b>	:	26-34 SECONDS #2 ZAHN CUP AT 20C
<b>PH RANGE</b>	:	8.6 – 9.4

### PACKAGING

Plastic Jugs	4 kg	8.8 lb
Plastic Kits	18 kg	39.6 lb
Drums	200 kg	440.0 lb